



EP 0 & 00

Spectra Lube EP 0 & 00 are lithium thickened semi-fluid greases containing EP/AW additives, antioxidants and corrosion inhibitors. Suitable for use in centralized lubrication systems that require semi-fluid grease due to its consistency. Typically used in lightly loaded gear boxes such as corn heads (NLGI #0) in agriculture and other industrial applications where NLGI #0 and #00 are recommended. NOT for use in heavy-duty truck trailer wheel hubs.

Typical Test Data

Test	Method	Spectra Lube EP 0	Spectra Lube EP 00
NLGI Grade	NLGI	#0	#00
Penetration @ 25°C W60	ASTM D-217	355-385	400-430
Thickener Type	---	Lithium	Lithium
Color	----	Amber	Amber
Appearance	Visual	Smooth, semi fluid	Smooth, semi fluid
Base Oil Viscosity, cSt @ 40°C	ASTM D445	150	150
Base Oil Viscosity, cSt @ 100°C	ASTM D445	14.6	14.6
Viscosity Index	ASTM D2270	95	95
Dropping Point (°C/ °F)	ASTM D2265	193°C/379°F	--
4-Ball EP, Weld Point, kg.	ASTM D2596	250	250
4-Ball Wear, mm scar dia.	ASTM D2266	.52	.52
Timken OK Load (lbs.)	ASTM D2509	40	40
Copper Corrosion Protection	ASTM D4048	1b	1b
Steel Corrosion Protection	ASTM D1743	Pass	Pass



EP 0 & 00

For high temperature considerations, in general first consider the actual temperature range of the application, is this application intermittent or continuous and what the reasonable re-lubrication intervals are. For low temperature operation grease distribution systems must be given proper consideration, pump type and capability, grease flow lines, length, type and size.

*Refer to OEM specifications and recommendations regarding product type and lubrication interval for the equipment being lubricated.

Product Availability

Item #	NLGI #0	Pack Type	Item #	NLGI #00	Pack Type
460757	SPECTRA LUBE EP 0	Pail 35 lb.	460760	SPECTRA LUBE EP 00	Pail 35 lb.
460758	SPECTRA LUBE EP 0	Keg 120 lb.	460761	SPECTRA LUBE EP 00	Keg 120 lb.
460759	SPECTRA LUBE EP 0	Drum 400 lb.	460762	SPECTRA LUBE EP 00	Drum 400 lb.