

FS THF Fluid

Description

FS THF Fluid is a high-quality, multifunctional fluid, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir. FS THF Fluid is formulated with high-viscosity-index base oils, viscosity index improver, anti-foam agent, pour point depressant, and a special additive package providing outstanding oxidation and corrosion inhibition, anti-wear properties, and frictional characteristics.

Features and Benefits:

- Lower operating costs
- Longer equipment life
- Chatter-free operation
- Compatibility
- Reduced downtime
- Smoother operation

Product Availability:

5 Gal. Pail	Item #155659
55-gal. Drum	Item #70699
265-gal. Totes	Item #70516
Bulk	Item #071041

Typical Properties:

Test / Description	Specification
Approximate SAE Grade	10W-20
Viscosity @ 100°C (cSt)	9.5
Viscosity @ 40°C (cSt)	63.5
Viscosity Index	130
Density (lb/gal)	7.20
CCS Viscosity (cP)	NA
Pour Point (°C)	-36
Pour Point (°F)	-33
Flash Point (°C)	215
Flash Point (°F)	419

Meets or Exceeds:

- API GL-4
- Allison C2, C4
- Caterpillar TO-2
- Clark Lift Trucks
- CNH MAT 3525,3526
- Deutz-Allis Power Fluid 821XL, 25741, 25743, 246634, 272843
- Fiat-Hesston AF-87
- Ford ESN-M2C-77A, 78A, 79A; ESN-M2C-86 A-C; ESN-M2C86A & C; ESN-M2C134A-D; FNHA-2-C-200, FNHA-2-C-201
- Industry of Machine and Tractor (IMT)
- JI Case Case-O-Matic Type A
- John Deer 303 (must also claim a verifiable specification such as J20C); J14A-C; J20A; J20B; J20C (meets); J20D; J21A
- Koti
- Kubota UDT, Super UDT, Super UDT2
- Landini
- Leyland (UTTO only)
- MF 1103 A&B; M1110; M1127,1127A&B; M1129 & M1129A (Permatran); M1135 (Permatran III); M1139(UTTO only); M1141; M1143; M1144 (UTTO only); M1145
- Quatrol
- Sauer Sunstrand/Danfoss Hydro Static Trans Fluid
- Sperry Vickers/Eaton I-286S; M2950S Mobile Hydraulics; M2952S Industrial Hydraulics
- Valmet
- Vickers 35VQ25
- Yanmar

Always check owner's manual for proper recommendation.

