

FS Suprex SAE 15W-40, 10W-30, 10W, 20W, 30, 40, & 50

Description

- Designed for heavy-duty two- and four-stroke diesel engines found in farm machinery, construction equipment, and marine and over-the-road use.
- Blended using specially selected, high-quality base oils and additives providing excellent detergency, dispersancy, oxidation stability, rust/ corrosion prevention, and foam suppression.
- Available in SAE viscosity grades 15W-40, 10W-30, 20W, 10W, 30, 40, and 50.
- Multi-viscosity 15W-40 and 10W-30 can eliminate seasonal grade changes in many areas and offer better fuel economy.

Meets or Exceeds:

10W

- API CD-II
- ACEA E3, B3, A3

10W-30

- API CK-4
- API CJ-4
- API CI-4
- API CG-4, CF-4
- API CD-II
- MACK EO-M Plus
- Caterpillar ECF-1
- ACEA E5
- ACEA E3, B3, A3
- Cummins 20077
- Volvo VDS-2

20W

- API CD-II

30

- API CF-2
- API CD-II
- Caterpillar TO-2

40

- API CF-2
- API CD-II
- ACEA E3, B3, A3

50

- API CF-2
- API CD-II

15W-40

- API CK-4
- API CJ-4
- API CI-4
- API CG-4, CF-4
- API CD-II
- API CF, CD, CE
- API SL, SJ
- MACK EOS-4.5, EO-O Premium Plus, EO-N
- Caterpillar ECF-1
- ACEA E5
- ACEA E3, B3, A3
- Allison C-4
- Cummins 20077
- Mercedes Benz 288.3, 229.1
- Volvo VDS-2
- Global DHD-1

*Always check the owner's manual for proper recommendations.

Product Availability:

FS SUPREX SAE 15W-40			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	155661	265-gal. Totes	15265
55-gal. Drum	15264	Bulk	15266

FS SUPREX SAE 10W-30			
Package Size	Item Number	Package Size	Item Number
5 Gal. Pail	302785	265-gal. Totes	302788
55-gal. Drum	302786	Bulk	167444

FS SUPREX SAE 10W			
Package Size	Item Number	Package Size	Item Number
55-gal. Drum	15269	Bulk	15271
265-gal. Totes	15270		

FS SUPREX SAE 20W			
Package Size	Item Number	Package Size	Item Number
55-gal. Drum	15274	Bulk	15276
265-gal. Totes	15275		

FS SUPREX SAE 30			
Package Size	Item Number	Package Size	Item Number
6 x 1 Qt.	015277	265-gal. Totes	15281
2 x 2.5 Gal.	15278	Bulk	15282
55-gal. Drum	15280		

FS SUPREX SAE 40			
Package Size	Item Number	Package Size	Item Number
55-gal. Drum	15285	Bulk	15287
265-gal. Totes	15286		

FS SUPREX SAE 50			
Package Size	Item Number	Package Size	Item Number
2 x 2.5 Gal.	15288	265-gal. Totes	199692
55-gal. Drum	15290	Bulk	153601

Typical Properties:

Test /Description	Specification						
SAE Grade	10W	10W-30	15W-40	20W	30	40	50
Viscosity @ 100°C (cSt)	6.5	11.0	15.0	7.5	11.0	14.4	19.0
Viscosity @ 40°C (cSt)	39.7	71.2	111.0	49.4	92.0	135.0	214.0
Viscosity Index	115	145	140	115	105	105	100
Density (lb/gal)	7.23	7.20	7.28	7.23	7.29	7.39	7.46
CCS Viscosity (cP)	3,000	5,500	6,000	1,100	NA	NA	NA
Pour Point (°C)	-36	-33	-33	-33	-27	-18	-12
Pour Point (°F)	-33	-27	-27	-27	-17	0	10
Flash Point (°C)	180	210	215	205	220	220	225
Flash Point (°F)	356	410	419	401	428	428	437
TB	10	10	10	10	10	10	10
Sulfated Ash	0.96%	0.96%	0.96%	0.96%	0.96%	0.96%	0.96%