



# FS CG 10 MS

## A light Duty Multi-purpose Oil

### PRODUCT APPLICATIONS

**FS CG 10 MS** has excellent cleanliness characteristics. The fluid is clear, very low odor and has a high flash point. This product may be used for light duty honing applications, and can be used to replace diesel fuel as a machining fluid. **FS CG 10 MS** is used straight. Do not dilute.

### TYPICAL PHYSICAL PROPERTIES

|                       |   |
|-----------------------|---|
| Fluid Type            | Straight Oil                                |
| Appearance            | clear colorless                             |
| Specific Gravity      | 0.84  |
| Flash Point C.O.C.    | above 248 F                                 |
| Weight per Gallon     | 7.10 lbs.                                   |
| Freeze Thaw Cycle     | Stable                                      |
| Metal Staining        | N/A, safe on ferrous and Non-ferrous metals |
| Viscosity @ 40°C, cSt | 2   |

**STORAGE:** **FS CG 10 MS** should be stored at room temperatures (between 55 to 95 °F). Keep away from sparks, open flames, and other sources of ignition as product and empty containers could contain combustible, flammable, or ignitable substances. Do not weld or cut empty drums.

**HEALTH & SAFETY:** Please refer to the Safety Data Sheet (SDS) for additional information.

**Warranty:** Because conditions of use are beyond our control no representation or warranty is made in connection with the use of this product. Technical information and recommendations are believed to be accurate but are not guaranteed.

June, 2015

R: Product Tech Letterhead 2015/FS CG 10 MS