



FS CG 4555

Rust Preventative (Straight Oil RP, Oil Film)

FS CG 4555 is a straight oil rust preventative that does not contain any solvent in the formulation. FS CG 4555 is considered a low VOC product which may help when looking to reduce carbon footprint and is an ideal choice when spraying agricultural equipment, construction equipment, or any indoor parts that may require an oily film.

FS CG 4555 is to be used straight, do not cut back with solvent, or dilute with any other oils. FS CG 4555 is not water soluble and will not mix with water.

TYPICAL PHYSICAL PROPERTIES

Fluid Type:	Rust Preventative
Specific Gravity:	0.90
Flash Point:	>395 Degrees F
Viscosity, cSt @ 40C:	70-65
ASTM Color:	3.0
Water Displacement:	Pass
Humidity Cabinet, ASTM D 1748:	1,848 Hours (77) Days
Indoor Protection:	30 Months Indoor Protection (2.5 Years)
Salt Spray, 5%, ASTM B117:	36 Hours
Acidic Atmosphere:	Pass- Up to 24 hours.
Nickel Metal Reactivity:	No nickel reaction in laboratory, test in field
Barium/ Heavy Metals:	Barium Free/ No heavy metals in product
Application:	Parts may be sprayed or dipped.

STORAGE: FS CG 4555 should be stored at room temperatures (between 55 to 95 °F). Keep away from sparks, open flames, and other sources of ignition as product and empty containers could contain combustible, flammable, or ignitable substances. Do not weld or cut empty drums.

HEALTH & SAFETY: Please refer to the Safety Data Sheet (SDS) for additional information.

Warranty: Because conditions of use are beyond our control no representation or warranty is made in connection with the use of this product. Technical information and recommendations are believed to be accurate but are not guaranteed.

July, 2015

R: Product Tech Letterhead 2015/CG 4555