

# FS Vacuum Pump Oil

## Description

FS Vacuum Pump Oil is designed for use in universal and other brands of vacuum pumps, including rotary vane and piston types. This oil is specially compounded from highly refined paraffinic base oils and a balanced additive package including anti-wear, antioxidant, rust inhibitor, demulsifier, and foam inhibitor additives. It possesses outstanding oxidation stability and demulsibility, especially in systems employing oil recovery. The low pour point ensures reliable operation in all weather conditions.

## Features and Benefits:

- Excellent rust/corrosion protection
- High oxidation stability
- Superior anti-wear performance
- Good viscosity characteristics
- Excellent demulsibility
- Anti-foam protection

## Product Availability:

### FS Vacuum Pump Oil

2 x 2.5 Gal.	Item #71103
55-gal. Drum	Item #71104
265-gal. Totes	Item #281323
Bulk	Item #174716

## Typical Properties:

Test / Description	Specification
SAE Grade (Approx.)	10
Viscosity @ 100°C (cSt)	6.4
Viscosity @ 40°C (cSt)	42.0
Viscosity Index	101
Density (lb/gal)	7.23
Pour Point (°C)	-36
Pour Point (°F)	-33
Flash Point (°C)	215
Flash Point (°F)	419
Oxidation Stability (hrs)	2,700+

